

FOLKEN GROTTENE

Production Specs - General Information

Venue Folken Grottene

Promoter Studentersamfunnet Folken

Visiting address Løkkeveien 24
4008 Stavanger
Norway

Postal address Postboks 632
4003 Stavanger
Norway

Vat ID NO970444459

Phone +47 515 64 444

Fax +47 515 64 441

E-mail folken@folken.no

Web www.folken.no

CONTACTS

Production Nora Alnes Teigen

E-mail nora@folken.no

Phone (cell) +47 932 96 850

Technical Steven Bishop

E-mail steven@folken.no

Phone (cell) +47 468 96 785

Booking Jesper Brodersen

E-mail jesper@folken.no

Phone (cell) +47 46822624

VARIOUS INFORMATION

Load-in

Behind venue. Stairway, no elevator.

Stagehands

As agreed

Parking

Behind venue. Landlines: 1
Bus Power: 32A 220V

Backstage

Small dressing room Prod. office: No
Washing Fac.: No

Internet

Wireless Internet Access

Access to stage

Through audience area.

Capacity

180 standing, 80 seated

Dinner

To be advanced with Production Manager

Stage measurements

Width (between speakers: 6,0 m
Stage height: 0,25 m
Depth: 3,5 m
Clearance: 2,25m

SOUND SYSTEM

PA

2 x L-Acoustics A15i Wide

2 x L-Acoustics SB18

1 x L-Acoustics LA-4X

FOH and IO

1 x Yamaha CL5 Mixing console

2 x Yamaha Rio1608 stagerack (32in/16out, analog)

MONITOR SYSTEM

8 x Martin LE100 12" LF / 1" HF Monitors

3 x Yamaha PX5 Amplifiers

6 mixes possible

MICROPHONES & DI

7 x Samson S-Direct, Active DI

4 x Shure SM58, Dynamic mic

2 x Shure SM57, Dynamic mic

1 x Shure Beta 52, Dynamic mic

1 x Shure Beta 91, Condenser mic

4 x Sennheiser E904, Dynamic mic

4 x Sennheiser E906, Dynamic mic

3 x AKG C535EB, Condenser mic

1 x AT ATM25, Dynamic mic

1 x AKG C480-61, Condenser mic

MICROPHONE STANDS

7 x K&M 210, Large tripod

2 x K&M 260, Large roundbase

8 x K&M 233, Small roundbase

LIGHT SPECS

1 x Okero 619 dimmer 6x13A

14 x Par56

4 x Strand Quartett fresnell

8 x Bright XLED HD, RGBWAUV Parcan

Lighting console: Varilite Zero88

PS: Static lights by default. Please get in touch if you need a light tech, or are bringing your own tech.

VARIOUS INFORMATION - LIGHT & STORAGE

Light grid

The light grid consists of a single tube on the back of stage and one on each side front of stage.

FOH

Lighting console: MA Lightcommander 12/2
One DMX line from FOH to stage dimmer, wavy access for more equipment

Haze

Use of haze or smoke is **NOT** allowed

Backdrop

There is no dedicated backdrop truss. Backdrop has to be attached to the light truss in the back.

All fabrics for stage use **must be fireproofed**.

Please bring the "white-papers" for the fabric, or bring a small "test-piece".

Storage

Very limited space for storage.